DSC

From Tyco Security Products

with PowerG Technology

Wireless PowerG Panic Key

PG4938

(Applicable to Brazil, Peru, Uruguay, Asia Pacific excluding China)



PowerSeries neo compatible

iotega compatible

Features That Make a Difference:

- **PowerG*** robust industry leading commercial grade wireless technology
- Visual acknowledgement of requested action
- Full two-second delay on panic button
- Long-life lithium batteries included
- Compatible with PowerSeries Neo systems

The power of PowerG*:

The power behind our latest products lies in various innovative technologies, including the revolutionary PowerG, which, bundled together, provide a robust and feature-rich platform designed to reduce operational costs for dealers and provide ultimate reliability for end users.

- Multichannel, Frequency Hopping Spread Spectrum technology - to overcome frequency blocking and interference
- Adaptive Transmission Power - for battery life preservation
- High transmission ranges - for reliable communication within up to 2km/2187 yards line-of-sight
- TDMA synchronized communication technology - to prevent message collisions
- 128 bit AES encryption - high level protection against analysis tools and digital attacks

Wireless PowerG PG4938 Panic Key

The PG4938 Wireless PowerG Panic Key is a portable personal protection device which allows users to send an emergency notification to the security system, via one large, easy-to-use button, thus alerting authorities. This attractive, compact and water-resistant panic key can be worn around the neck or permanently mounted/clipped to a belt with the multifunction clip.

Visual Indication

When the button of the PG4938 is pressed, the visual LED indicator confirms the command has been successfully carried out by the security system. The confirmation that the message has been executed by the security system offers ‘peace of mind’ to users.

False Alarm Reduction

The PG4938 is equipped with a full two-second activation delay to help reduce false alarms, thus minimizing costly false dispatches caused by accidental activations.

Easy To Use

With only a single, large and clearly defined panic button, the PG4938 allows for trouble-free activation in stressful emergency situations. Portable and simple to use, it allows users to call for support from anywhere within the premises.

DSC

From Tyco Security Products

Specifications:

Dimensions:..... 53 x 33 x 11mm (2.1 x 1.3 x 0.4in)

Battery Life: .....5 years (Typical usage)

Battery Type: 3V, CR2032

Weight: 15g (0.5oz)

Operating Temperature: .. -10°C to 55°C (14°F to 131°F)

Approvals:

FCC/IC, UL/ULC, CE, C-Tick, ANATEL, WPC, IDA

Please refer to www.dsc.com for the most current approval listings.
Product varies depending on country.

Compatibility:

PowerSeries Neo and iotega systems

PN 30001732R001

For product information
www.dsc.com

Product specifications and availability subject to change without notice. Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.
©2018 Tyco Security Products